

# CI-IWHDLCR

The **CI-IWHDLCR** is a state-of-the-art in-wall system.

An excellent match for large screen TV's or front projection main LCR's, its performance level places it in a rare echelon of in-wall speakers that rivals the sound of the best floor standing models. Features include an aluminum outer edge flange supporting a  $\frac{3}{4}$ " thick MDF mounting baffle for maximum rigidity and efficiency, proprietary cast Quiet Cone™ wool/carbon bass woofers, Seas™ Reed cone midrange and a Dyna 1" silk dome tweeter. This driver complement, coupled to a HT (high transfer) – Minimum Phase crossover and proprietary interior sound deadening materials, provides outstanding lateral sound stage, inner resolution, and sound field depth with excellent dynamics and power bandwidth.



## SPECS DESCRIPTION CI-IWHDCLR

System Design	Three-Way Reference grade in-wall LCR
Enclosure	Sealed
Woofer	(2) 8" CWC cone
Midrange	(1) 7" Reed cone
Tweeter	(1) 1" Silk dome
Recommended Amp Power	50-400 W
Frequency Response	45 Hz - 20 kHz
Anechoic Frequency Response	45 Hz - 20 kHz +/- 2 dB
Impedance	4 ohms
Sensitivity (db 1 watt/1 meter)	89
Hole Cut Out	12.25" x 39" x 6"d
Overall Size	13.25" x 40"
Standard Finish	Satin Black