

# CI-IW10RS / CI-IW10RS-PRO



The CI-IW10RS / 10RS-PRO, designed for 2x4 construction applications, utilizes extremely limited rear cavity airspace to produce the deepest octaves with speed, clarity and definition.

## FEATURES INCLUDE:

- Cast frame 10" long throw bass driver (RS) / dual drivers (RS-PRO)
- Rigid enclosure
- Performance rivals competitors free standing floor subwoofers with excellent room efficiency and bass power
- 32hz (RS) 28 hz (RS-PRO) frequency response
- 4 ohm
- Only 3.95" d to fit 2x4 construction



SPECS DESCRIPTION	SPECS
System Design	Sealed
Woofer	10" Subwoofer for 2x4 Construction
Driver	10" Driver (Dual PRO) W/ 3" VC Cast Frame, Neodymium
Amplifier	50 - 350 / 700 (PRO) W RMS
Frequency Response / Max SPL	32 Hz – 120 Hz / 112 spl 18 Hz – 120 Hz / 118 spl (PRO)
Sensitivity	91 / 96 (PRO) dB @ 1 w @ 1 m
Dimensions	OD 16" h x 16" w / 32.75" x 16".25 (PRO)   Hole 13.5" x 13.5" / 30.5" x 14" (PRO)