

# IN-CABINET SUBWOOFER



**Hidden within Cabinet ("HC")** subwoofer systems offer the highest level of performance when the installation environment requires positioning the subwoofer inside a concealed cabinet. The proprietary downward firing bandpass design delivers ultra-clean bass frequencies with higher SPL's by concentrating the output through a vented slot located in the side of the enclosure.

Choose from a variety of standard and custom dimension options. Port will start 1/2" from the bottom, not including the rubber isolation feet.

## FEATURES INCLUDE:

- Downward-firing bandpass design
- Slotted vent for optimal bass extraction
- Delivers clean bass through an installed toe kick system
- Modification available to fire through a cloth grille cabinet door
- Large rubber isolation feet provided
- Gasket tape provided to further isolate the enclosure from the cabinet construction
- Custom sizes available to match most cabinet openings

CI-HC10	SPECS
System Design	Subwoofer, Down firing, Bandpass
Driver	10" Peerless SLS long throw
Amplifier	300 W RMS (available w/ 300 watt amp or passive)
Frequency Response	32 Hz – 120 Hz / 108 spl
Sensitivity	94 dB @ 1 watt
Standard Finish	Black Pro Duratex
Dimensions	24" h x 12" d x 12" w

CI-HC12	SPECS
System Design	Subwoofer, Down firing, Bandpass
Driver	12" Peerless SLS long throw
Amplifier	300 W RMS (available w/ 300 watt amp or passive)
Frequency Response	27 Hz – 120 Hz / 115 spl
Sensitivity	94 dB @ 1 watt
Standard Finish	Black Pro Duratex
Dimensions	30" h x 13.5" d x 13.5" w