



OWNER'S MANUAL

IN-CABINET SUBWOOFER

Installation • Amplifier Setup • Safety • Warranty



CAUTION

To reduce the risk of electric shock and fire, do not remove the inner cover below the top plate or the back plate of this device. There are no user serviceable parts inside. Please refer all servicing to licensed service technicians.

The international symbol of a lightning bolt inside a triangle is intended to alert the user to uninsulated “dangerous voltage” within the device’s enclosure. The international symbol of an exclamation point inside a triangle is intended to alert the user to the presence of important operating, maintenance and servicing information in the manual accompanying the device.

CAUTION! To prevent electrical shock, match wide blade of plug to wide slot, fully insert. CAUTION! To reduce the risk of electrical shock, do not expose this equipment to rain or moisture.

- 1 Read Instructions—All safety and operating instructions should be read before operating the device.
- 2 Retain Instructions—The safety and operating instructions should be retained for future reference.
- 3 Heed Warnings—All warnings on the device and in the operating instructions should be adhered to.
- 4 Follow Instructions—All operating and safety instructions should be followed.
- 5 Water & Moisture—The device should never be used in, on or near water for risk of fatal shock.
- 6 Stands—The device is not intended to be used on a stand.
- 7 Ventilation—The device should always be located in such a way that it maintains proper ventilation. It should never be placed in a built-in installation or anywhere that may impede the flow of air around the product.
- 8 Heat—Never locate the device near heat sources such as radiators, floor registers, stoves or other heat-generating devices.

- 9 Power Supply—The device should only be connected to a power supply of the type described in the operating instructions or as marked on the device.
- 10 Power Cord Protection—Power cables should be routed so they are not likely to be stepped on or crushed by items placed on them or against them. Special attention should be paid to areas where the plug enters a socket or fused strip and where the cord exits the device.
- 11 Cleaning—The device should be cleaned in accordance with manufacturer's instructions.
- 12 Periods Of Non-Use—The device should be unplugged when not being used for extended periods.
- 13 Dangerous Entry—Care should be taken that no foreign objects or liquids fall or are spilled inside the device.
- 14 Damage Requiring Service—The device should be serviced by licensed technicians when:
 - The plug or power supply cord has been damaged.
 - Objects have fallen, or liquid spilled inside of the device.
 - The device has been exposed to moisture.
 - The device does not appear to be operating properly or exhibits a marked change in performance.
 - The device has been dropped or the cabinet becomes damaged.
- 15 Service—The device should always be serviced by licensed technicians. Only replacement parts specified by the manufacturer should be used. The use of unauthorized substitutions may result in fire, shock, or other hazards.

SERVICE NOTE

If service is required, use a licensed technician and manufacturer-specified replacement parts.

Amplifier Settings

300 W AMPLIFIER

Please follow the 300 W amplifier settings below:

LEVEL CONTROL

Generally 10–11 o'clock, not higher

FREQUENCY / LOW PASS


9–10 o'clock

LOW PASS

9–10 o'clock

PHASE

0–180° — adjust for max output



IMPORTANT: Using settings greater than 12 o'clock could cause failure.

A: Volume

Controls subwoofer level. This amplifier has a very high gain. Set the level @ 10–11 o'clock or lower.

B: Low Pass

Controls the amount of mid-bass. Normal setting is about half-way up.

C: Phase

Variable from "0" to "180". Slowly turn until you hear optimal bass response.

D: Phono Inputs ("Line-in")

Feed signal to the subwoofer from the receiver connected directly to the "Sub Out" on the receiver.

E: Speaker Level Inputs

Speaker-level input connection.

IN-CABINET SUBWOOFER PERFORMANCE

The HC10, our 10" Hidden within Cabinet ("HC") subwoofer system offers the highest level of performance when the installation environment requires positioning the subwoofer inside a concealed cabinet. The proprietary downward-firing bandpass design delivers ultra-clean bass frequencies with higher SPL's by concentrating the output through a vented slot located in the side of the enclosure.



IN-CABINET SUBWOOFER INSTALLATION

1

Place the in-cabinet subwoofer into the cabinet so that the slotted port fires out either a toe-kick or the intended opening (preferably unobstructed). Use the provided gasket tape to decouple the subwoofer from whatever material it may come in contact with during installation.

ADDITIONAL INFORMATION

- Wall Outlet: In the US 110V – 20-amp service preferred as 12-gauge wire, used for 20-amp service, provides a better draw supply to the amplifier. There is a slight improvement in tightness and bass speed going from 16 amp to 20 amp.
- Rubber feet are included to provide isolation between bottom of sub and floor. This isolation is necessary for clean bass.
- Subwoofer response is complex and room interactive. In addition, there is a break in period of about 2 weeks to attain best performance.

CONTENTS

☐ In-Cabinet Subwoofer

☐ Power Cord

☐ Rubber Feet (4)

☐ Product Manual

Limited Warranty

COVERAGE & EXCLUSIONS

5 YEARS

Drivers and Cabinets

2 YEARS

Amplifiers

90 DAYS

Exterior fit & finish

Coverage: 5-Years for Drivers and Cabinets, 2-years on amplifiers for any defects or performance issues realized during the product's normal use, and 90 days for defects in manufacture or workmanship covering the exterior fit and finish for peeling and cracks.

JS Speaker Technology, LLC (herein "JS Speaker Technology"), warrants to the original retail purchaser only that products manufactured by JS Speaker Technology (the "Product") will be free from defects in material and workmanship for a period of five (5) years covering drivers and cabinets, 2-years on amplifiers, and ninety (90) days covering the exterior fit and finish for peeling and cracks from the date of the original purchase from a JS Speaker Technology Authorized Dealer. If the Product is defective in material or workmanship, JS Speaker Technology or its Authorized Dealer will, at its option, repair or replace the warranted product at no additional charge, except as set forth below. All replaced parts and Product(s) become the property of JS Speaker Technology. The product that is repaired or replaced under this warranty will be returned to you, within a reasonable time, freight collect. This warranty is non-transferable and is automatically void if the original purchaser sells or otherwise transfers the Product to any other party. This Warranty does not include service or parts to repair damage caused by accident, misuse, abuse, negligence, inadequate packing or shipping procedures, commercial use, voltage in excess of the rated maximum of the unit, cosmetic appearance of cabinetry not directly attributable to defects in material or workmanship. This warranty does not cover the elimination of externally generated static or noise, or the correction of antenna problems or weak reception. This warranty does not cover labor costs or damage to the Product caused by installation or removal of the Product. JS Speaker Technology makes no warranty with respect to its products purchased from dealers or outlets other than JS Speaker Technology Authorized Dealer.

WARRANTY VOID CONDITIONS & SERVICE

The warranty is automatically void if: 1) The product has been damaged, altered in any way, mishandled during transportation, or tampered with. 2) The product is damaged due to accident, fire, flood, unreasonable use, misuse, abuse, customer applied cleaners, failure to observe manufacturers warnings, neglect or related events. 3) Repair or modification of the Product has not been made or authorized by JS Speaker Technology. 4) The product has been improperly installed or used. The product must be returned (insured and prepaid), together with the original dated proof of purchase to the Authorized Dealer from whom the Product was purchased, or to the nearest JS Speaker Technology factory service center. The product must be shipped in the original shipping container or its equivalent. JS Speaker Technology is not responsible or liable for loss or damage to the Product in transit.

LIMITATIONS & LEGAL TERMS

This limited warranty is the only express warranty that applies to your product. JS Speaker Technology neither assumes nor authorizes any person or entity to assume for it any other obligation or liability in connection with your product or this warranty. All other warranties, including but not limited to express, implied, warranty of merchantability or fitness for a particular purpose, are expressly excluded and disclaimed to the maximum extent allowed by law. All implied warranties on products are limited to the duration of this expressed warranty. JS Speaker Technology has no liability for acts of third parties. JS Speaker Technology's liability, whether based on contract, tort, strict liability, or any other theory, shall not exceed the purchase price of the product for which a claim has been made. Under no circumstance will JS Speaker Technology bear any liability for incidental, consequential, or special damages. The consumer agrees and consents that all disputes between the consumer and JS Speaker Technology shall be resolved in accordance with Connecticut in Hartford County, Connecticut. JS Speaker Technology reserves the right to modify this warranty statement at any time. Some states do not allow the exclusion or limitation of consequential or incidental damages or implied warranties, so the above limitations may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.



THANK YOU

for choosing NextLevel Acoustics

SUPPORT

(617) 237-2875

www.nextlevelacoustics.com